



MSP Ducted Fan Coil Unit FWQ-A










BLDC fan motor and open
protocol control capability

Fan Coil Unit

Medium Static Pressure ducted unit with BLDC fan motor

The new FWQ-A fan coil expands the ducted FCU portfolio with **advanced performance and versatility**. Offering a cooling capacity from 2.1 to 11.5 kW across 9 different sizes, it is designed to meet the needs of a wide range of applications. Every unit is equipped as standard with an integrated drain pump and an additional sub-drain pan, ensuring **safe & reliable operation**. Engineered for **maximum flexibility**, the FWQ-A is the ideal choice for modern HVAC solutions.

Green Building Certification: Supporting BREEAM & LEED Standards

	BREEAM					LEED	
Category							
Credits	Up to 4	Up to 4	Up to 9	Up to 2	Up to 1	Up to 4	Up to 1

Shinka FCU Control System


Designed for smart and intuitive operation, the Shinka control system can be connected with the FWQ-A units for optimized performance. This integrated system delivers maximum efficiency and comfort with minimal setup effort, further simplified by the Daikin Shinka Manager **Commissioning mobile app**.



Benefits




Variable Dip Switch
for efficient unit size selection
and reduced investment




**Brushless Direct Current
motor** high comfort with lower
operating costs



Open protocol communication
for an efficient system
management



Easy & fast installation thanks
to factory-mounted valves and
integrated drain pump



Flexible air filtration with
the option to upgrade standard
filters